


KEMET, FLLD4-TH, EMI/RFI Filters, Noise Suppression, 530 VAC, 25 A, 130x125x115mm



General Information	
Series:	FLLD4-TH
Style:	Chassis Mount
Description:	EMI Filter, Chassis Mount, Compact
Features:	High Performance
Phase:	Three-phase + Neutral
RoHS:	Yes
Qualifications:	IEC/EN 60939
Terminal Type:	Terminal Block

Dimensions	
L	130mm NOM
W	125mm NOM
H	115mm NOM
L1	90mm NOM
W1	137.5mm NOM
W2	153mm NOM
J	32mm NOM
K	6.5mm NOM
M (Earth)	Threaded Studs M6

Specifications	
Voltage AC:	530 VAC
Rated Frequency:	50-60 Hz
Rated Current:	25 A (50°C)
Rated Temperature:	50°C
Temperature Range:	-25/+100°C
Climate Category:	25/100/21
Test Voltage DC (P to P):	2250 VDC
Test Voltage DC (P to E):	3000 VDC
Power Loss:	12 W (25°C 50 Hz)
Leakage Current:	11 mA

Packaging Specifications	
Packaging:	Bulk
Packaging Quantity:	1
Component Weight:	1.2 kg

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.