

Specification Sheet

Part Number: 156-00306

Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point.

2-piece design allows installer to slide clip around cable tie to obtain optimum orientation

Clip is reusable, making relocation or adjustments simple.



2-Piece Cable Tie with Pipe Clip, 50lbs, Clip Dia .16"-.4" Max Bun Dia. 1.38" PA66HS Tie, HIRHS MNT, BLK 500/pkg

Article Number 156-00306

Type T50ROC1B

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's 2-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.

Short Description 2-Piece Cable Tie with Pipe Clip, 50lbs, Clip Dia .16"-.4" Max Bun Dia. 1.38" PA66HS Tie, HIRHS MNT, BLK 500/pkg

Global Part Name T50ROC1B-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 8.0

Length L (Metric) 202.0

Fixation Method Omega Clips

Identification Plate Position none

Tie Closure plastic pawl

Width W (Imperial) 0.181

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.16

Bundle Diameter Min (Metric) 4.0

Bundle Diameter Max (Imperial) 1.8

Bundle Diameter Max (Metric) 45.0

Thickness T (Imperial) 0.05

Thickness T (Metric) 1.2

Height H (Imperial)	0.05
Height H (Metric)	1.2
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

