

## Specification Sheet

Part Number: T50R9VOM4



Feature a UL 94 V-0 rating to comply with low flame and smoke requirements.

Inside serrations provide strong grip on cables and wire bundles.

Easy application either manually or with a tensioning tool.

Bent tail ensures a quick and simple installation.

Flame Retardant Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66V0, Natural, 1000/pkg

**Article Number** 111-04911

**Type** T50R

**Color** Natural (NA)

**Quantity Per** bag

**Product Description** HellermannTyton's flame retardant cable ties meet the UL 94 V-0 flammability requirements. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Flame Retardant Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66V0, Natural, 1000/pkg

**Global Part Name** T50R-PA66V0-NA

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 225.0

**Length L (Imperial)** 8.0

**Length L (Metric)** 202.0

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.18

**Width W (Metric)** 4.6

**Bundle Diameter Min (Imperial)** 0.12

**Bundle Diameter Min (Metric)** 3.0

**Bundle Diameter Max (Imperial)** 1.97

**Bundle Diameter Max (Metric)** 50.0

**Thickness T (Imperial)** 0.05

<b>Thickness T (Metric)</b>	1.2
<b>Material</b>	Polyamide 6.6 V0 (PA66V0)
<b>Material Shortcut</b>	PA66V0
<b>Flammability</b>	UL 94 V-0
<b>Operating Temperature</b>	-40°F to +212°F (-40°C to +100°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-ZODZ2.E64139
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988

