


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00543	Connector, dc jack, 5.5x2.5x17.6 mm, molding style, spring contacts, nickel plated, 105° C	1	
2	30-00795	Wire, 2C TS, 18 AWG, UL2651, 300V, 105C, 4.4 mm, VW-1, PVC, red and black	1	
3	24-00004	Overmold, PVC	1	black, 105° C, 94V-0



Wiring Diagram	
50-00543	wire color
center	red
sleeve	black

Notes:
Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	12/6/2016	Initial release	AG <small>Digitally signed by AG Date: 2017.08.03 09:56:58 -07'00'</small>		
			Verified:	Function test: no open, no short circuit, no intermittent	Size:
			LA <small>Digitally signed by LA Date: 2017.08.03 14:30:50 -07'00'</small>	Description:	A
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, 5.5x2.5 mm 50-00543 dc jack to 10 mm tinned, 18 AWG, 30-00795 R-B wire, 105° C	Part number: 10-02324
					Scale: 1:1
					Sheet 1 of 1

5

↑

4

3

2

1