



**Product:** [8762](#)

Electronic, 2 C #20 Str TC, PE Ins, OS, PVC Jkt, CM

[Request Sample](#)

## Product Description

Electronic, 2 Conductor 20AWG (7x28) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM, Suitable for Audio, Control, and Instrumentation Applications

## Technical Specifications

### Product Overview

|                        |   |
|------------------------|---|
| Suitable Applications: | low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring |
|------------------------|---|

### Construction Details

#### Conductor

| Element | Number of Element | Size   | Stranding | Material           |
|---------|-------------------|--------|-----------|--------------------|
| Pair(s) | 1                 | 20 AWG | 7x28      | TC - Tinned Copper |

#### Insulation

| Element | Material          | Nom. Thickness     | Color Code   |
|---------|-------------------|--------------------|--------------|
| Pair(s) | PE - Polyethylene | 0.017 in (0.43 mm) | Black, Clear |

#### Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type   |
|-------------|-------------------------|----------|------------------|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 20 AWG (7x28) TC |

#### Outer Jacket

| Material                 | Nom. Thickness     | Nom. Diameter      |
|--------------------------|--------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.028 in (0.71 mm) | 0.204 in (5.18 mm) |

|                                   |                    |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.204 in (5.18 mm) |
|-----------------------------------|--------------------|

### Electrical Characteristics

#### Electricals

| Element | Nom. Conductor DCR         | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Nom. Characteristic Impedance | Max. Current                   |
|---------|----------------------------|-------------------------------|---|-------------------------------|--------------------------------|
| Pair(s) | 9.5 Ohm/1000ft (31 Ohm/km) | 27 pF/ft (89 pF/m)            | 49 pF/ft (160 pF/m)                             | 56 Ohm                        | 3.9 Amps per Conductor at 25°C |

#### Voltage

| UL Voltage Rating                |
|----------------------------------|
| 300 V (CM), 300 V (UL AWM 2092)) |

### Mechanical Characteristics

#### Temperature

| UL Temperature     | Operating      |
|--------------------|----------------|
| 60°C (UL AWM 2092) | -20°C to +60°C |

#### Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
|                 |                   |

|                |                |
|----------------|----------------|
| 2.0 in (51 mm) | 2.0 in (51 mm) |
|----------------|----------------|

|                    |                          |
|--------------------|--------------------------|
| Max. Pull Tension: | 38 lbs                   |
| Bulk Cable Weight: | 21 lbs/1000ft (31 kg/km) |

## Standards and Compliance

|                                  |   |
|----------------------------------|---|
| Environmental Suitability:       | Indoor  |
| Flammability / Reaction to Fire: | UL1685 UL Loading, IEC 60332-1-2  |
| CPR Compliance:                  | CPR Euroclass: Eca  |
| NEC / UL Compliance:             | Article 800, CM   |
| AWM Compliance:                  | UL AWM Style 2092   |
| CEC / C(UL) Compliance:          | CM  |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |

## History

|                      |  |
|----------------------|--|
| Update and Revision: | Revision Number: 0.382 Revision Date: 12-15-2021 |
|----------------------|--|

## Variants

| Item #        | Color  | Putup Type | Length    | UPC/EAN       |
|---------------|--------|------------|-----------|---------------|
| 8762 060100   | Chrome | Reel       | 100 ft    | 612825215363  |
| 8762.00U152   | Chrome | UnReel     | 152 m     | 8719605019059 |
| 8762.01152    | Chrome | Reel       | 152 m     | 8719605019073 |
| 8762 060250   | Chrome | Reel       | 250 ft    | 612825215400  |
| 8762.00U305   | Chrome | UnReel     | 305 m     | 8719605019066 |
| 8762.01305    | Chrome | Reel       | 305 m     | 8719605019080 |
| 8762 060500   | Chrome | Reel       | 500 ft    | 612825215417  |
| 8762 060U500  | Chrome | UnReel     | 500 ft    | 612825215356  |
| 8762.01610    | Chrome | Reel       | 610 m     | 8719605019097 |
| 8762 0601000  | Chrome | Reel       | 1,000 ft  | 612825215370  |
| 8762 060U1000 | Chrome | UnReel     | 1,000 ft  | 612825215349  |
| 8762 0602000  | Chrome | Reel       | 2,000 ft  | 612825215394  |
| 8762 06010000 | Chrome | Reel       | 10,000 ft | 612825215387  |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.