

## L6R200D Series

# 200W Desktop Power Supply

- DOE Level VI Efficiency Rating
- Universal Input: 90 ~ 264Vac, 47/63 Hz
- UL/cUL/IEC 62368-1 Approved
- Corded Output Connection
- IEC 60320 C6 and C14 AC input connectors
- Light Weight and Compact
- RoHS Compliant Class II Design



Model No. <sup>1</sup>	Application	Output Connector	Output Voltage	Output Current (A)			Voltage Accuracy	Ripple Noise	Line Reg.	Load Reg.
				Min	Rated	Peak				
L6R200D-120	ITE	4-Pin Circular DIN	+12.0V	0	16.00	—	±5%	< ± 2%	± 1%	± 5%
L6R200D-135	ITE	4-Pin Circular DIN	+13.5V	0	14.00	—	±5%	< ± 2%	± 1%	± 5%
L6R200D-190	ITE	4-Pin Circular DIN	+19.0V	0	10.50	—	±5%	< ± 2%	± 1%	± 5%
L6R200D-240	ITE	4-Pin Circular DIN	+24.0V	0	8.30	—	±5%	< ± 2%	± 1%	± 5%
L6R200D-480	ITE	4-Pin Circular DIN	+48.0V	0	4.17	—	±5%	< ± 2%	± 1%	± 5%
L6R200D-560	ITE	4-Pin Circular DIN	+56.0V	0	3.58	—	±5%	< ± 2%	± 1%	± 5%

1. Add "C6" or "C14" for the required AC input connector configuration.

- The output voltage is verified to specs at 60 percent rated load condition.
- The **line regulation** is defined by changing ± 10 percent of input voltage from the nominal line at rated load.
- The **load regulation** is defined by changing ± 40 percent of the measured output load from 60 percent of the rated load.
- The **ripple and noise** is measured by using 20MHz bandwidth limited oscilloscope with each output terminated with a 10 µF electrolytic and a 0.1 µF capacitor at rated load and nominal line.
- The **efficiency** is measured at rated load and nominal line.

# L6R200D Series

Innovative, reliable, and inexpensive. This economical, Class II design is a DOE Level VI compliant power supply/charger is available in a variety of voltage levels, 12.0 to 56.0Vdc (per the

model number table) to match your needs. Rated up to 200W when powering either stationary or charging portable devices.

## Specifications

### Input

Input Voltage	• 90 Vac ~ 264 Vac
Input Frequency	• 47 Hz to 63 Hz
No Load Input Power	• < 0.15W
Input Current	• 2.8A Max.
Inrush Current	• 60A Max. / 230Vac
Leakage Current	• 3.5mA Max.
Input Connection	• IEC 60320 C6 or C14

### Output

Output Voltage Range	• 12.0 to 56.0Vdc
Output Current Range	• 16.0 to 3.58A
Minimum Load	• No min. load required.
Line Regulation	• $\pm 1\%$ at rated load across input voltage range
Load Regulation	• $\pm 5\%$ (typical)
Ripple & Noise	• 2% Vp-p Max. @ full load
Overvoltage Protection	• Auto recovery
Overload Protection	• Auto recovery
Short Circuit Protection	• Auto recovery

### General

Dielectric Withstand	• 3,000Vac Primary to Secondary
Efficiency	• Level VI, ErP Stage 2, CoC Tier 2 compliant
MTBF	• 300,000 hrs. @ 25°C per Telcordia SR-332

### Environmental

Operating Temperature	• 0°C to 40°C
Operating Humidity	• 20 to 80% RH, Non-Condensing
Storage Temperature	• -20°C to +80°C
Storage Humidity	• 10 to 90%, Non-Condensing

### EMC & Safety

Safety Approvals	• UL/cUL: UL/cUL 62368-1, 60950-1
	• CE: IEC 62368-1, 60950-1
EMC Approvals	• FCC

### Warranty

Warranty Period	• 1 year
-----------------	----------

### Dimensions and Notes

Dimensions in mm	
Tolerance	• $\pm 0.2\text{mm}$
Size	• L 183 x W 81 x H 42 (mm) L 7.20" x W 3.19" x H 1.65"
Weight	• Approx. 850g (1.87 lb.) (Ref.)
Connectors	• AC input; IEC 60320 C6 or C14 connector
	• DC output; 4-pin circular DIN output connector or per customer specification.
Output Cord length	• L6R200D-120 & -135: 1200 $\pm$ 30 mm (47.2 $\pm$ 1.2") All other P/Ns: 1500 $\pm$ 30 mm (59 $\pm$ 1.2")

## Mechanical Drawing

