

USB-C to DVI Adapter with USB-A Port and PD Charging, White

MODEL NUMBER: **U444-06N-DU-C**



Adds DVI, USB-A and USB-C PD charging ports to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC.

Features

Turn Your Device's USB-C Port into a Multiport Workstation Ideal for transmitting video to a large display, adding a USB peripheral, and powering and charging a PD Charging-compliant mobile device simultaneously. Plug-and-play operation with no software, drivers or external power required. About the size of a credit card for easy carrying in a pocket, purse or laptop bag.

Transmit Crystal-Clear 1080p Video to DVI Display Compatible with USB-C or Thunderbolt 3 source devices that support USB DisplayPort Alternate Mode. Supports DVI single-link video resolutions up to 1920 x 1080 (1080p) @ 60 Hz. Supports DVI digital transfer rates up to 6.75 Gbps (2.25 Gbps per channel). Extends video from your primary display to another. Duplicates the same video on 2 displays. Converts a secondary display to your primary display.

Connect a USB Peripheral USB-A port accepts flash drives, mice, keyboards, printers and other USB peripherals. Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps. Backward compatible with USB 2.0 and USB 1.1. BC 1.2-compliant port provides up to 1.5A of fast-charging power to mobile devices. Note: Host must support USB OTG (On-the-Go).

Charge a Connected Device USB-C PD port connects to wall charger to power and charge the connected PD Charging-compliant USB-C/Thunderbolt 3 device. Supports power input up to 20V 3A (60W). Note: USB-C PD port does not support Quick Charge (QC).

Built-In Cable with Reversible USB-C Connector Fumble-free reversible USB-C plug connects in either direction for quick connection every time.

Specifications

OVERVIEW	
UPC Code	037332193902

Highlights

- Supports USB DisplayPort Alternate Mode for transmitting video
- Supports DVI video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- PD Charging port supports power input up to 20V 3A
- BC 1.2-compliant USB-A port provides up to 1.5A of fast-charging power
- Reversible USB-C plug connects in either direction
- Plug-and-play operation with no software or drivers required

Applications

- Transmit 1080p video to a DVI display via the USB-C port on your laptop, computer or tablet
- Charge the host device with up to 60 watts of power via the PD Charging port

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with DVI input (DVI port)

Package Includes

- U444-06N-DU-C USB 3.1 Gen 1 USB-C to DVI Adapter
- Owner's manual



Product Type	USB-C to DVI Adapter
Technology	DVI
Host Connector	USB C (MALE)
VIDEO	
Video Input	USB C (MALE)
Video Output	DVI-I DUAL LINK (FEMALE)
Number of Monitors Supported	1
Video Ports	DVI-I DUAL LINK (FEMALE)
Video Ports Details	HDCP 1.3
Resolutions Supported	1920 x 1080 @ 60 Hz (1080p)
Supported Resolutions	1280x720 (720p); 1920x1080 (1080p)
Max Supported Video Resolution	DVI: 1920 X 1080 (1080P) @ 60HZ
Extended Mode	No
Mirror Mode	No
3D Video Supported	No
DATA	
Data Ports	USB A (FEMALE)
Data Ports Details	USB-A - USB 3.2 Gen 1 (5 Gbps)
INPUT	
Built-In Cable Length (ft.)	0.36
Built-In Cable Length (m)	11.0
Built-In Cable Length (in.)	4.33
Bus Powered	Yes
Product Length (in.)	6
Product Length (cm.)	15.24
Product Length (ft.)	0.5
Product Length (m.)	0.15
BATTERY	
Battery Charging (5V/1.5A Port)	Yes
POWER	
USB Power Delivery (PD) Charging Support	Yes



USB Power Delivery (PD) Charging Specification	2.0
CHARGING	
Total Charging Watts	60
Charging Ports Details	20V/3A (60W) PD Charging
Charging Ports	USB-A: 5V 1.5A (7.5W); USB-C: 60W (20V 3A) Power Delivery (PD 2.0)
Charging Ports / Amps	1.5A; 3A
PHYSICAL	
Color	White
Material of Construction	Plastic
Cable Jacket Rating	VW-1
Shipping Dimensions (hwd / cm)	2.29 x 11.18 x 14.22
Shipping Dimensions (hwd / in.)	0.90 x 4.40 x 5.60
Shipping Weight (kg)	0.18
Shipping Weight (lbs.)	0.40
Unit Dimensions (hwd / in.)	0.57 x 3.1 x 1.6
Unit Packaging Type	Box
Unit Weight (kg)	0.04
Unit Weight (lbs.)	0.08
ENVIRONMENTAL	
Operating Temperature Range	32 to 113 °F (0 to 45 °C)
Storage Temperature Range	14 to 158 °F (-10 to 70 °C)
BTUs	4.1 BTU/Hr
Power Consumption (Watts)	1.2
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
Power Provided to Connected Device(s)	5V 0.9A (4.5W) Output (USB-A), Up to 20V 3A (60W) Input (USB-C)
CONNECTIONS	
Ports	3
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	DVI-I DUAL-LINK (FEMALE) (WIRED TO DVI-D SINGLE-LINK)
Side B - Connector 2	USB 3.0 A (FEMALE)
Side B - Connector 3	USB C (FEMALE)



Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
HDCP Specification	1.3
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
UASP Support	No
Auto MDIX Support	No
Full Duplex Support	No
Suspend Mode Support	No
Remote Wakeup Support	No
STANDARDS & COMPLIANCE	
Certifications	CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>