

**PB-DP SUB-D****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

**General ordering data**

Type	PB-DP SUB-D
Order No.	<a href="#">839550000</a>
Version	Sensor/Actuator plug-in connector
GTIN (EAN)	4008190394646
Qty.	1 pc(s).

## PB-DP SUB-D

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Net weight	51 g
------------	------

### Technical specifications for sub-D connector

Data rate	12 Mbit/s	Housing main material	PC UL 94 V-1
Humidity	Max. 75% at +25°C, non-condensing	Interlock	UNC4-40
Outgoing elbow	90°	PROFIBUS DP interface	D-Sub 9-pole
Plug-in connector and pin assignment	In accordance with the PROFIBUS specification	Protection degree	IP 40
Temperature range of housing	-25...+80 °C		

### Classifications

ETIM 3.0	EC000830	UNSPSC	30-21-18-01
eClass 6.2	27-06-91-90	eClass 7.1	27-06-91-90

### Approvals

Approvals	
ROHS	Conform