



**Product:** [8760](#)

Electronic, 2 C #18 Str TC, PE Ins, OS, PVC Jkt, CM

[Request Sample](#)

**Product Description**

Electronic, 2 Conductor 18AWG (16x30) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

**Technical Specifications**

**Product Overview**

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring
------------------------	---

**Construction Details**

**Conductor**

Element	Number of Element	Size	Stranding	Material
Pair(s)	1	18 AWG	16x30	TC - Tinned Copper

**Insulation**

Element	Material	Nom. Thickness	Color Code
Pair(s)	PE - Polyethylene	0.018 in (0.46 mm)	Black, Clear

**Outer Shield**

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	20 AWG (7x28) TC

**Outer Jacket**

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.028 in (0.71 mm)	0.222 in (5.64 mm)

Overall Cable Diameter (Nominal): 0.222 in (5.64 mm)

**Electrical Characteristics**

**Electricals**

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Pair(s)	6.5 Ohm/1000ft (21 Ohm/km)	27.2 pF/ft (89.2 pF/m)	7.2 Amps per Conductor at 25°C

**Voltage**

UL Voltage Rating
300 V (CM), 300 V (UL AWM 2092))

**Mechanical Characteristics**

**Temperature**

UL Temperature	Operating
60°C (UL AWM 2092)	-20°C to +60°C

**Bend Radius**

Stationary Min.	Installation Min.
2.2 in (56 mm)	2.2 in (56 mm)

Max. Pull Tension: 54 lbs (24 kg)

Bulk Cable Weight:	25 lbs/1000ft (37 kg/km)
--------------------	--------------------------

## Standards and Compliance

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	UL1685 UL Loading, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CM
AWM Compliance:	AWM 2092
CEC / C(UL) Compliance:	CM
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
Plenum Number:	88760, 87760 or 82760

## History

Update and Revision:	Revision Number: 0.403 Revision Date: 02-08-2022
----------------------	--

## Part Numbers

### Variants

Item #	Color	Putup Type	Length	UPC/EAN
8760.01152	Chrome	Reel	152 m	8719605018809
8760 060250	Chrome	Reel	250 ft	612825215189
8760.01305	Chrome	Reel	305 m	8719605018823
8760 060500	Chrome	Reel	500 ft	612825215196
8760 060U500	Chrome	UnReel	500 ft	612825215127
8760 0601000	Chrome	Reel	1,000 ft	612825215134
8760 060U1000	Chrome	UnReel	1,000 ft	612825215110
8760 0602000	Chrome	Reel	2,000 ft	612825215172
8760 0605000	Chrome	Reel	5,000 ft	612825215202
8760 06010000	Chrome	Reel	10,000 ft	612825215141
8760 06015000	Chrome	Reel	15,000 ft	612825215165
8760.00U152	Gray	UnReel	152 m	8719605018793
8760.01U305	Gray	UnReel	305 m	8719605018830
8760.00610	Gray	Reel	610 m	8719605018786
8760.011525	Gray	Reel	1,525 m	8719605018816

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.