


S43LCC0403 THRU S43LCC0424 TVS ARRAY



Description

The S43LCCXX series of TVS array have been designed to provide bidirectional protection for sensitive electronics from damage due to voltage transients caused by electrostatic discharge (ESD), electrical fast transients (EFT), secondary lightning and other voltage-induced transient events. The device can be used to protect 1 bidirectional or interface line.

Schematic & Pin Configuration



Features

- Protects 3.3,5,12,15,24 V Components
- Bidirectional
- Ultra Low Capacitance 15 pF
- Ultra Low Leakage
- Provides Electrically Isolated Protection
- 500 W @ 8/20 us
- Protects 1 Line
- “-A” is an AEC-Q101 qualified device
- SOT-143 Packaging
- This is a Pb - Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

Mechanical Characteristics

- SOT-143 Surface Mount Package
- Approximate Weight: 0.03 grams
- PIN #1 Indicator: DOT on top of package
- Packaging: Tape and Reel Per EIA 481

Application

- LAN/WAN Equipment
- Cellular Phone
- Notebooks, Desktops, & Servers
- Audio/Video Inputs
- Handheld Electronics
- Fire Wire, SCSI & USB interfaces

Maximum Ratings@ $T_A=25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Value	Units
Peak Pulse Power, 8/20 μs Wave shape	P	500	W
Operating Temperature	T_J	-55 to +125	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-55 to +150	$^{\circ}\text{C}$
Lead Soldering Temperature	T_L	260 (10 Sec.)	$^{\circ}\text{C}$

Electrical Characteristics@T_A=25°C unless otherwise specified

Part Number	Device Code	Stand-off Voltage V _{wm} (V) Max	Breakdown Voltage V _{BR} @1mA (V) Min	Clamping Voltage V _c @ 1 A (V) Max	Leakage Current I _R @ V _{wm} (uA) Max	Capacitance (f = 1MHz) C @ 0V (pF) Max	Temperature Coefficient of V _{BR} a(V _{BR}) mv/°C Max
S43LCC0403	L03	3.3	4	8	200	15	-5
S43LCC0405	L05	5.0	6	10.8	40	15	1
S43LCC0412	L12	12.0	13.3	19	1	15	8
S43LCC0415	L15	15.0	16.7	24	1	15	11
S43LCC0424	L24	24.0	26.7	43	1	15	28

Ratings and Characteristics Curves




Figure 1. Peak Pulse Power Vs Pulse Time (µs)





Figure 2. Pulse Wave Form

Ordering Information

Device	Package	Shipping
S43LCC0403 THRU S43LCC0424	SOT-143 (Pb-Free)	3000pcs / reel
S43LCC0403TR THRU S43LCC0424TR	SOT-143 (Pb-Free)	3000pcs / reel


Marking Diagram



For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.


- China - Germany - Korea - Singapore - United States •
- <http://www.smc-diodes.com> - sales@smc-diodes.com •

Mechanical Dimensions SOT-143



SYMBOL	Millimeters		Inches	
	MIN.	MAX.	MIN.	MAX.
A	0.890	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.076	0.170	0.003	0.007
D	2.650	3.050	0.104	0.120
E	1.190	1.400	0.047	0.055
E1	2.100	2.550	0.083	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.780	2.050	0.070	0.081
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

Carrier Tape Specification SOT-143



SYMBOL	Millimeters	
	Min.	Max.
A	3.09	3.29
B	2.70	2.90
C	1.21	1.41
d	1.40	1.60
E	1.65	1.85
F	3.40	3.60
P	3.90	4.10
P0	3.90	4.10
P1	1.90	2.10
W	7.90	8.10

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..