



CATHODE & GATE LEAD KITS



1. WIRE COMPOSITION:
 AWG 22, TINNED COPPER STRANDED WIRE WITH ETEF INSULATION RATED TO 125° C.
2. LEAD COLOR:
 RED (CATHODE) AND YELLOW (GATE). RED LEAD IS POSITIONED NEXT TO KEY ON BLACK POLARIZED HOUSING.
3. RECEPTACLES:
 FEMALE TERMINAL WITH LOCKING TAB FITS .11 x .03 IN. BLADES.

LEAD KIT TO ORDER	ORDER FOR MODULE	DESCRIPTION
LEAD KIT #NK	LD43-ND43-CD63-PD43 (FULL CONTROL)	LEAD SET 1 & LEAD SET 2 – ONE EACH/MODULE
LEAD KIT #NL	LD42-LS43-ND42-CD62 (HALF CONTROL)	LEAD SET 1 – ONE/MODULE
LEAD KIT #NM	LD47-ND47-CD67-PS43 (HALF CONTROL)	LEAD SET 2 – ONE/MODULE



1. WIRE COMPOSITION:
 AWG 22, TINNED COPPER STRANDED WIRE WITH ETEF INSULATION RATED TO 125° C.
2. LEAD COLORS:
 RED (CATHODE) AND YELLOW (GATE). BOTH WITH INSULATED TERMINALS.
3. RECEPTACLES:
 FEMALE TERMINAL WITH NYLON INSULATOR THAT FITS .11 x .03 IN. BLADE.

LEAD KIT TO ORDER	ORDER FOR MODULE	DESCRIPTION
LEAD KIT #MQ	CD43 (FULL CONTROL)	TWO RED & TWO YELLOW LEADS PER MODULE.
LEAD KIT #MR	CD42-CD47 (HALF CONTROL)	ONE RED AND ONE YELLOW LEAD PER MODULE