



(B)

- NOTES:
1. MATERIAL: AS NOTED
  2. FINISH: AS NOTED
  3. ELECTRICAL:  
VOLTAGE: 600VAC  
CURRENT: 25A
  4. TEMP RATING: -20°C TO +90°C
  5. CSA CERTIFIED FILE: LR6837
  6. UL RECOGNIZED FILE: E46237
  7. ALL DIMS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE

MATERIAL NO.	ENGINEERING NO.	CHAIN LENGTH
1300190003	22803	1 FT. (0.31 M)
1300190004	22804	2 FT. (0.61 M)
1300190005	22805	3 FT. (0.91 M)

ITEM	DESCRIPTION	MATERIAL	FINISH
5	CHAIN	STEEL	ZINC PLATE
4	YOKE	STEEL	ZINC PLATE
3	#10 X 1/2 RD HD DRIVE SCREW	STEEL	ZINC PLATE
2	SPACER TUBE	CRS	
1	SHORTING PLUG ASSEMBLY	Cu ALLOY (PIN)	YELLOW

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS  
 $\nabla_A = 0$   
 $\nabla_E = 0$   
 $\nabla_S = 0$

DIVISIONAL SYMBOLS

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

CURRENT REV DESC: ADDED NOTES

EC NO: 711366  
 DRWN: VHANDI 2021/12/22  
 CHK'D: RSTONE 2022/06/21  
 APPR: BWOODMAN 2022/06/24

INITIAL REVISION:  
 DRWN: RSTONE 2013/01/15  
 APPR: JFMURPHY 2013/03/01

GENERAL TOLERANCES (UNLESS SPECIFIED)

	MM	INCH
4 PLACES	±	±
3 PLACES	±	±
2 PLACES	±	±
1 PLACE	±	±
0 PLACES	±	±

ANGULAR TOL ± °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

THIRD ANGLE PROJECTION

DRAWING B-SIZE

SERIES 130019

MATERIAL NUMBER SEE TABLE

CUSTOMER GENERAL MARKET

SHEET NUMBER 1 OF 1

**molex**

DIE BLOCK  
SHORTING PLUG ASSEMBLY 2 POLE, FEMALE

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER SD-130019-002

DOC TYPE PSD

DOC PART 001

REVISION B