



TECHNICAL

| | |
|-----------------------|-----------------------|
| AGENCY APPROVAL: | cULus |
| RATED SUPPLY VOLTAGE: | 120VAC |
| RATED CURRENT: | 15A |
| RESET TYPE: | MANUAL |
| OPERATING FREQUENCY: | 60 Hz |
| TYPE: | CLASS A |
| GROUND TRIP CURRENT: | 4-6 mA |
| OVERLOAD CURRENT: | 90 AMP |
| INSULATION VOLTAGE: | 1,500 VRMS - 1 MINUTE |
| ENDURANCE OPERATIONS: | 3000 OPERATIONS |
| ENCLOSURE: | NEMA 3R |

| MATERIAL NUMBER | ENGINEERING NUMBER | LENGTH "A" | LENGTH "L" |
|-----------------|--------------------|------------------|-----------------|
| 1301530054 | 15052-1 | 9.50 IN. | 1 FT 11.4 IN. |
| 1301530067 | 15052-6 | 4 FT. 10.50 IN. | 6 FT. 0.4 IN. |
| 1301530060 | 15052-25 | 23 FT. 10.50 IN. | 25 FT. 0.4 IN. |
| 1301530064 | 15052-50 | 48 FT. 10.50 IN. | 50 FT. 0.4 IN. |
| 1301530055 | 15052-100 | 98 FT. 10.50 IN. | 100 FT. 0.4 IN. |

| | | | | | | |
|--|---|--|---|---|-------------------------------|--|
| FUNCTIONAL SYMBOLS $\nabla/\square = 0$ $\nabla/\square = 0$ $\nabla/\square = 0$ | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | <div style="text-align: center;">molex</div> GFCI IN-LINE 15A W/WATERTITE PLUG & CONNECTOR | | | |
| | DIMENSION UNITS | SCALE | | | | |
| | INCH NTS | | GENERAL TOLERANCES (UNLESS SPECIFIED) | | EC NO: 693149 | |
| | ANGULAR TOL ± ° | | 4 PLACES ± | | DRWN: PPURSUTANDEL 2021/12/29 | |
| DIVISIONAL SYMBOLS | | 3 PLACES ± | | CHKD: DNGUYEN62 2022/01/26 | | |
| 2 PLACES ± | | 1 PLACE ± | | APPR: HKNEELAND 2022/04/28 | | |
| 0 PLACES ± | | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | INITIAL REVISION: DRWN: PPURSUTANDEL 2019/07/26 | | |
| THIRD ANGLE PROJECTION | | DRAWING | | APPR: HKNEELAND 2020/09/16 | | |
| B-SIZE | | SERIES | | DOCUMENT NUMBER | | |
| 130153 | | MATERIAL NUMBER | | 1301530067 | | |
| SEE TABLE | | CUSTOMER | | DOC TYPE DOC PART REVISION | | |
| GENERAL MARKET | | SHEET NUMBER | | PSD 000 B | | |
| 1 OF 1 | | | | | | |