



NEMA 5-15  
SUPER-SAFEWAY  
PART NO. 1447  
COLOR: YELLOW

NEMA 5-15  
SUPER-SAFEWAY  
PART NO. 1547  
COLOR: YELLOW

#12-3 STJW, 300V CORD  
COLOR: YELLOW

**TECHNICAL:**  
 LISTED: cULus  
 RATED SUPPLY VOLTAGE: 120 VAC  
 RATED CURRENT: UP TO 15 AMPS OR CABLE RATING  
 RESET TYPE: AUTOMATIC OR MANUAL  
 OPERATING FREQUENCY: 60 Hz  
 TYPE: CLASS A  
 GROUND TRIP CURRENT: 4-6 mA  
 OVERLOAD CURRENT: 90 AMP 125 VAC  
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE  
 ENDURANCE OPERATIONS: 3000 OPERATIONS

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	LENGTH "A"	POWER-UP
1301530043	15051-1A	2 FT 7 IN	1 FT ± 1 IN	AUTO
1301530052	15051-6A	7 FT 7 IN	6 FT ± 2 IN	AUTO
1301530046	15051-25A	26 FT 7 IN	25 FT ± 2 IN	AUTO
1301530049	15051-50A	51 FT 7 IN	50 FT ± 4 IN	AUTO
1301530044	15051-1M	2 FT 7 IN	1 FT ± 1 IN	MANUAL
1301530053	15051-6M	7 FT 7 IN	6 FT ± 2 IN	MANUAL
1301530047	15051-25M	26 FT 7 IN	25 FT ± 2 IN	MANUAL
1301530050	15051-50M	51 FT 7 IN	50 FT ± 4 IN	MANUAL

FUNCTIONAL SYMBOLS FA = 0 FC = 0 FD = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: MIGRATION TO ECTR/NX	
	DIMENSION UNITS <b>INCH</b>	SCALE <b>NTS</b>		
DIVISIONAL SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)			
	ANGULAR TOL ± 0.5°			
	4 PLACES	±	EC NO: 684571	
	3 PLACES	±	DRWN: VASUTHKARP	2021/11/08
	2 PLACES	± 0.13	CHK'D: DNGUYEN62	2022/01/20
1 PLACE	± 0.25	APPR: HKNEELAND	2022/02/02	
0 PLACES	±	INITIAL REVISION:		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRWING	SERIES
			<b>D-SIZE</b>	<b>130153</b>
		MATERIAL NUMBER		CUSTOMER
		<b>SD-130153-015</b>		<b>GENERAL MARKET</b>
		DOCUMENT NUMBER	DOC TYPE	DOC PART
		<b>PSD</b>	<b>001</b>	<b>A1</b>
		SHEET NUMBER		<b>1 OF 1</b>