

CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART.

NOTES:

1. BLACK FRAME.
2. BLACK BACKGROUND.
3. PIXEL COLOR: YELLOW.
4. MINIMUM VIEWING ANGLE OF 65 DEGREE FROM 12,3,6 & 9 O'CLOCK.
5. WISECHIP SEMI US2066 CONTROLLER.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION

UNCONTROLLED DOCUMENT



425 N. GARY AVE.
CAROL STREAM, IL 60188-4900
PHONE: +1.800.278.5666
FAX: +1.630.315.2152
WEB: www.itwecs.com

5.57mm CHARACTER HEIGHT, 5x8 DOT MATRIX, 16x2 OLED MODULE, YELLOW PIXELS, 5.0 v, HIGH TEMP.


THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE:	06.09.14	DRAWN BY:	MA
PAGE:	DF 2	CHKD BY:	KF
SCALE:	NTS	APRVD BY:	--
UNIT:	mm [INCH]		Ⓟ

PIN CONFIGURATION

PIN NO.	SYMBOL	LEVEL	DESCRIPTION
1	Vss	0V	SUPPLY VOLTAGE FOR LOGIC GROUND
2	VDD	5.0V	SUPPLY VOLTAGE FOR LOGIC
3	NC	-	
4	RS	H/L	H:DATA, L: INSTRUCTION CODE
5	R/W	H/L	H:READ (MPU-->MODULE);L:WRITE(MPU-->MODULE)
6	E	H,H->L	CHIP ENABLE SIGNAL
7	DB0	H/L	DATA BIT 0
8	DB1	H/L	DATA BIT 1
9	DB2	H/L	DATA BIT 2
10	DB3	H/L	DATA BIT 3
11	DB4	H/L	DATA BIT 4
12	DB5	H/L	DATA BIT 5
13	DB6	H/L	DATA BIT 6
14	DB7	H/L	DATA BIT 7
15	Vcc	12.0V	SUPPLY VOLTAGE FOR PANEL(POSITIVE VOLTAGE OUTPUT)
16	NC	-	



ELECTRICAL/OPTO CHARACTERISTICS

VDD=5V , TA=25°C

ITEM	SYMBOL	CONDITION	STANDARD VALUE			UNIT
			MIN.	TYP.	MAX.	
SUPPLY VOLTAGE FOR LOGIC	VDD-Vss	-	4.7		5.3	V
SUPPLY VOLTAGE FOR PANEL	Vcc-Vss	-	7.0	12.0	12.5	V
INPUT VOLTAGE	HIGH	V _{IH}	0.8VDD	-	VDD	V
	LOW	V _{IL}	0	-	0.2VDD	V
OUTPUT VOLTAGE	HIGH	V _{OH}	0.9VDD	-	VDD	V
	LOW	V _{OL}	0	-	0.1VDD	V
OLED DRIVING CURRENT	IDD	-	-	*50	-	mA
VIEW ANGLE				FREE		
DARK ROOM CONTRAST				>10000:1		
C.I.E. (C.I.E. 1931)	X	-	0.46	0.5	0.54	-
	Y	-	0.45	0.49	0.53	-
RESPONSE TIME					30	ns
BRIGHTNESS W/POLARIZER			60	100		cd/m ²

*BRIGHTNESS=100cd/m² , Ta=25°C, 60% RH, VDD=5.0V, VCC=12.0V, 100% DISPLAY AREA TURN ON.

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	TEST CONDITION	STANDARD VALUE		UNIT
			MIN	MAX	
SUPPLY VOLTAGE FOR LOGIC	VDD-Vss	Ta=25°C	2.4	5.5	V
SUPPLY VOLTAGE FOR PANEL	VCC-VSS	Ta=25°C	7	13	V
HUMIDITY			-	85	%
OPERATING TEMPERATURE*	Topr	-	-40	80	°C
STORAGE TEMPERATURE	Tstg	-	-40	90	°C

OPERATING LIFE 50,000 HRS
END OF LIFE IS SPECIFIED AS 50 %OF INITIAL BRIGHTNESS

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= ^{+0.00}DECIMAL PRECISION MAX.= ^{-0.00}DECIMAL PRECISION



425 N. GARY AVE.
CAROL STREAM, IL 60188-4900
PHONE: +1.800.278.5666
FAX: +1.630.315.2152
WEB: www.itweccs.com

5.57mm CHARACTER HEIGHT,5x8 DOT MATRIX,OLED 16x2 LCD MODULE,YELLOW,1/16DUTY,1/5 BIAS,3.3v,HIGH TEMP.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE:	06.09.14	DRAWN BY:	MA
PAGE:	2 OF 2	CHKD BY:	KF
SCALE:	NTS	APRVD BY:	--
UNIT:	mm [INCH]		Ⓟ